




Republic of the Philippines
UNIVERSITY OF RIZAL SYSTEM
Province of Rizal

 Tel/Fax 653-2860
urs.spmo@gmail.com

June 10, 2019

Company/ Suppliers Name : _____

Address : _____

Please quote your lowest price on the item/s listed below, subject to the General Conditions on the last page, stating the shortest time of delivery and submit your sealed quotation duly signed by your representative not later than June 17, 2019 to URS SPMO, Morong Rizal.


NELSON S. GONZALES, Ed. D.
Chairperson, BAC

- NOTE: 1. ALL ENTRIES MUST BE TYPEWRITTEN
2. DELIVERY PERIOD WITHIN 30 CALENDAR DAYS
3. WARRANTY SHALL BE FOR A PERIOD OF SIX (6) MONTHS FOR SUPPLIES & MATERIALS, ONE (1) YEAR FOR EQUIPMENT, FROM DATE OF ACCEPTANCE BY THE ENTITY
4. PRICE VALIDITY SHALL BE FOR A PERIOD OF 45 CALENDAR DAYS
5. G-EPS REGISTRATION CERTIFICATE SHALL BE ATTACHED UPON SUBMISSION OF THE QUOTATION
6. BIDDERS SHALL SUBMIT ORIGINAL BROCHURES SHOWING CERTIFICATIONS OF THE PRODUCT BEING OFFERED

ITEM NO.	ITEM & DESCRIPTION	QTY.	UNIT	BID PRICE	TOTAL BID PRICE
1	Active Speaker, TS312, 2000-WATT 12-INCH 2-WAY POWERED LOUDSPEAKER, 2000 W peak (1300 LF + 700 HF) 1000 W continuous RMS (650 LF + 350 HF), 12-inch (305 mm) LF driver, 3-inch (76 mm) high-temperature voice coil, 1.4-inch (35 mm) neodymium magnet HF driver with precision wave guide, High quality, lightweight, cabinet design for easy transport, set up and installation, Pole-mountable, wedge monitor, bracket installation or flown application with integral M10 suspension points, Integrated 2-channel mixer with dual XLR 1/4-inch combo mic/line inputs, independent level controls, XLR Link output, Contour EQ switch and Ground-Lift switch, Custom-engineered high-efficiency class D amplifiers with passive cooling design – no fan means the speaker runs cleaner, quieter and has greater long-term reliability, Design Origin: Designed and tuned in the USA	4	Unit		
2	Active Powered Sub Woofer, TS SUB15, ACTIVE 1200 WATT 15" SUBWOOFER, 1200 Watts Class D power, Powerful 15" low-frequency, long-excursion driver, Stereo inputs: Mic/Line left channel, XLR right channel, Stereo XLR outputs: Left link, Right mono, internal 120Hz crossover on through, 18 mm birch plywood vented cabinet with metal grille and recessed handles, Adjustable level and polarity controls, 35 mm pole socket	2	Unit		
3	16 Channel Mixer with Effects, LIVE 1604, PROFESSIONAL 16-CHANNEL/4-BUS MIXER, 10 XLR inputs with DNA(TM) microphone preamps, Dynamic compression (channels 1-6), 3-band EQ with sweepable mids, 4 aux sends; pre/post switching on sends 1+2, 60mm faders with mute and PFL/AFL solo functions, 100 Alesis DSP effects, USB audio connectivity with level control, Balanced XLR, balanced/unbalanced 1/4" outputs,	1	Unit		

	Headphone out with independent level control, Switchable Phantom Power				
4	LED Par 54 Full Color, 8 Channel DMX-512 LED PAR 54 light, Built-in automated programs via stand alone mode by Menu Button, Built-in sound activated programs via sound activated, Master/slave, Individual control of red, green and blue LEDs RGBW, macros, run/strobe speed, automatic/sound, dimmer, Color gradual change/color jump change/strobe, running speed adjustment With fan, Low noise, good heat dissipation effect	8	Unit		
5	Mic Cable Nobelle, 100MT MIC CABLE. SAME QUALITY AS NOBELLE (Stereo)	3	Unit		
6	31 Band per Channel Equalizer, AEQ231, STEREO 31-BAND GRAPHIC EQ, Balanced XLR, 1/4" TRS and RCA input and output connectors, 1/3-octave spacing provides precise, sound-shaping control, Standard 20 mm center-detented sliders allow easy frequency adjustment, Selectable boost/cut range of 6 dB or 12 dB for more precise gain control, High-pass filter: 40 Hz (12 dB/octave), Low-pass filter: 16 kHz (12 dB/octave), Variable input level control, EQ bypass switch on both channels, Ground lift switch to disconnect signal ground from chassis ground, Clip level indicators	1	Unit		
7	8 Channel Mixer with Effects, ZMX122FX, 16 total inputs including XLR jacks w/ phantom power on ch. 1-4, On-board Alesis digital effects with 256 variations, Expanded channel count perfect for small groups or sub-mixes, 4 mic input channels with gold-plated XLR and balanced line inputs, Two stereo input channels with balanced TRS jacks, High headroom circuitry offering extra dynamic range, Ultra-low-noise discrete mic preamps, 3-band EQ on each channel, Footswitch input for effects on/off (sold separately), 2 aux sends per channel for external effects and monitoring, 2-bus design with Main and Control Room 1/4" stereo outputs, Aux inputs/outputs for external audio source integration	1	Unit		
8	Speaker Stand, Superior air cushion design. prevent any accidental slide and lowers gently, heavy duty steel construction. large leg rubber cover, steel tripod leg fitting, high quality plastic tripod leg fitting with metal tightening collar, steel leg housing	6	Unit		
	*** URSB ***				
	ABC – Php 258,390.00				

Brand and Model : _____ Delivery Period : _____
Warranty : _____ Price Validity : _____

After having carefully read and accepted your General Condition, I/We quote you on the items at prices noted above.

CERTIFICATION

I hereby certify that I have personally conducted this canvass and that the price(s) quoted is/are true & correct and the signature of the representative of the company who submitted the quotation(s) is/are genuine.

Posted at PhilGEPS

Printed Name & Signature of Authorized Canvasser

P.R. No.:2019-06-1051

Control No.: _____

PhilGeps Ref. No.: _____

Printed Name / Signature

Tel. No. / Cell phone No.

E-mail address

Date

Tin Number