



Republic of the Philippines
UNIVERSITY OF RIZAL SYSTEM
Province of Rizal

Cp No. (83)918-9519618
urs.bacsecretariat2020@gmail.com

Date : AUG. 22, 2024

Company/Supplier Name : _____

Address : _____

Please quote your lowest price on the item/s listed below, subject to the General Conditions on the last page, stating the shortest time of delivery and submit your sealed quotation duly signed by your representative not later than AUG. 27, 2024 5PMO, Morong Rizal.

ARIEL M. PLANTILLA, DBA
Chairperson, BAC

- NOTE: 1. ALL ENTRIES MUST BE TYPEWRITTEN
2. DELIVERY PERIOD WITHIN 20 CALENDAR DAYS
3. WARRANTY SHALL BE FOR A PERIOD OF SIX (6) MONTHS FOR SUPPLIES & MATERIALS, ONE (1) YEAR FOR EQUIPMENT, FROM DATE OF ACCEPTANCE BY THE ENTITY
4. PRICE VALIDITY SHALL BE FOR A PERIOD OF 45 CALENDAR DAYS
5. G-EPIS REGISTRATION CERTIFICATE SHALL BE ATTACHED UPON SUBMISSION OF THE QUOTATION
6. BIDDERS SHALL SUBMIT ORIGINAL BROCHURES SHOWING CERTIFICATIONS OF THE PRODUCT BEING OFFERED

ITEM NO.	ITEM & DESCRIPTION	QTY.	UNIT	BID PRICE	TOTAL BID PRICE
1	R32 Refrigerant in Reusable Tank (2kg)	1	pc(s)		
2	REFRIGERANT FREON R22 (13.6kg)	1	pc(s)		
3	REFRIGERANT Freon R410a 11.3kg	1	pc(s)		
4	SERVICE VALVE FOR AIRCON Access Valve with 1/4 copper connection	9	pc(s)		
5	CAPACITOR DUAL 50+3 UF +- 5% For ACU Application	2	pc(s)		
6	CAPACITOR DUAL 40 0R 45 +3 UF +- 5% For ACU Application	2	pc(s)		
7	CAPACITOR DUAL 25+3 UF +- 5% For ACU Application	2	pc(s)		
8	CLAW HAMMER (8oz) • Drop-forged carbon steel hammerhead • Heat treatment, ground polished • Fiberglass handle	1	pc(s)		
9	Lineman's Combination Pliers 200mm/8" • Forged carbon steel jaws fully heat treated for optimum performance and durability • Induction hardened cutting edges for greater reliability in cutting • Bi-material soft grip handle provides excellent comfort • Ergonomically designed DYNAGRIP™ handle with finger guards for better efficiency and handling	1	pc(s)		
10	Insulated Diagonal Cutting Plier / Side Cutter 8" FVDE Pliers are fully TÜV, GS and VDE certified, meaning they are guaranteed safe for working with electrical equipment up to AC 1000V or DC 1500V. Their induction hardened cutting edges stay sharp longer, and their machined jaws are	1	pc(s)		

	<p>designed for maximum gripping strength. Plus, their ProTouch™ grips provide extra comfort for less hand fatigue.</p> <p>Induction hardened cutting edges designed to stay sharper longer for wire cutting.</p>				
11	<p>VDE Insulated Long Nose Pliers 1000V (6")</p> <p>Premium Line VDE, GS Certified</p> <p>VDE/GS certificated</p> <ul style="list-style-type: none"> • Manufactured according to EN60900 • Metal part made in CRV steel • Black finished and polished surface • Precision machined body with strictly heat treatment • Heavy two-component insulated handles with slip guards for extra comfort and safety 	1	pc(s)		
12	<p>Cushion Grip 6pcs Screw Driver Set</p> <p>1 x Phillips: 1 X 100 mm</p> <p>1 x Philips: 2 X 150mm</p> <p>1 x Slotted Parallel: 5mm X 100mm</p> <p>1 x Slotted Parallel: 5mm X 150mm</p> <p>1 x Slotted: 6.5mm X 150mm</p> <p>1 x Slotted: 5mm X 100mm</p>	1	set(s)		
13	<p>6PCS INSULATED SCREWDRIVERS SET</p> <ul style="list-style-type: none"> • 0.4*2.5*75mm; 0.8*4.0*100mm; 1.0*5.5*125mm; • Insulated phillips screwdrivers: • PH0*60mm; PH1*80mm; • 3.0*70mm voltage tester; • VDE/GS certificated • Manufactured according to EN60900 	1	set(s)		
14	<p>PORTABLE PRESURE WASHER</p> <p>Wash and Rinse Nozzle</p> <p>Push Fit Connection</p> <p>High Pressure Foam (350ml)</p> <p>Compact Hose Storage</p> <p>Watts: 1300 W</p> <p>Pressure Rating: 110Bar</p> <p>Flow Rate: 330l/h</p> <p>Water Filter (New): Black</p> <p>Max Temp: 40c</p> <p>Hose: 3 m</p>	1	set(s)		
15	<p>Pressure Washer/Power Sprayer Set</p> <p>Heavy Duty</p> <p>Belt Driven</p> <p>Specifications Spraying Irrigation</p> <p>Pressure (kg/cm2) 21-35 0-10</p> <p>Suction (l/min) 14 20</p> <p>Rotation per minute (rpm) 800 1200</p> <p>Power (Motor) 1.5 HP</p> <p>Japan Technology</p> <p>Contents:</p> <ul style="list-style-type: none"> * Electric Motor 1.5 Horse Power * Piston Pump * 10m Discharge Hose * 2m Suction Hose * 2m Return Hose * Sprayer Straight (**Choose if you want long or short) * Base 	1	set(s)		
16	<p>Portable Paint Sprayer</p> <p>Powered by a 600 wattsmotor</p> <p>Supplied with 1.8 meters of air hose and comfort grip spray gun</p> <p>2 meters of power cable</p> <p>Adjustable nozzle provide 3 different type of spray patters: Vertical, Horizontal, and circular.</p> <p>Adjustable knob to regulate paint flow.</p> <p>Shoulder strap for easy carrying around while working</p>	1	set(s)		
17	<p>Combination Wrench Set</p> <p>FEATURES:</p>	1	set(s)		

	<p>Made from Drop forged, heat treated s2 tool steel</p> <p>Corrosion-resistant chrome plated finish</p> <p>Precision machined 15-degree angled open ends and 12-point offset box ends</p> <p>INCLUDED SIZES: 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 32mm</p>				
18	<p>SOCKET WRENCH SET 1/2 SIZE</p> <p>Includes:</p> <p>1 x 1/2" Quick Release Ratcheting Drive, 72 tooth, ergonomic cushion grip, CrV</p> <p>2 x 1/2" Extension 125mm & 250mm</p> <p>1 x 1/2" Universal Joint, CrV</p> <p>2 x 1/2" Spark Plug Sockets: 16mm and 21mm with rubber lining</p> <p>18 x SuperLock Sockets: Sizes: 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 27, 30 and 32mm,</p> <p>1 x 1/2" Sliding T-Handle</p>	1	set(s)		
19	<p>ROTARY HAMMER SDS DRILL 790WATTS</p> <p>SPECIFICATIONS:</p> <p>Impact rate at rated speed 0 – 4,200 bpm</p> <p>Rated speed 0 – 930 rpm</p> <p>Rated input power 790 W</p> <p>Impact energy (according to EPTA 05/2016) 2.7 J</p> <p>Weight 2.8 kg</p> <p>Max. drilling diameter in metal 13 mm</p> <p>Max. drilling diameter in wood 30 mm</p>	1	pc(s)		
20	<p>Digital Multi Tester</p> <p>3-3 / 4 digits 4000 count</p> <p>0.7% best accuracy</p> <p>Capacitance measurement * Not suitable for measurement of condensers with large leak current.</p> <p>Frequency measurement (AC sine wave only)</p> <p>Data hold / Range hold</p> <p>Relative value</p> <p>Auto power off (30min.) (cancelable)</p> <p>Low power ohm (input voltage 0.4V) at continuity range</p> <p>Solid & protective body cover that can also be used as a tilt stand</p> <p>Chip holder behind the body cover</p> <p>Display : numeral display 4000</p> <p>Sampling rate : 3 times / sec.</p> <p>AC frequency bandwidth : 40?400Hz</p>	1	pc(s)		
21	<p>Digital Clamp Multi Meter / Tester</p> <p>True RMS</p> <p>Measurable AC 0.1A?600A</p> <p>ACV & Resistance measurement</p> <p>Small Design & easy to carry</p> <p>Data hold</p> <p>Continuity check buzzer</p> <p>Sampling rate : approx.2 times / sec.</p> <p>AC frequency bandwidth : 50?400Hz</p>	1	pc(s)		
22	<p>Analog MULTI TESTER</p> <p>Analogue meter featuring null (zero center) capability</p> <p>Drop/Shock proof taut band movement</p> <p>Null meter facility: $\pm 5/\pm 25$ Vdc</p> <p>Resistance measurement up to 200MΩ</p> <p>Capacitance measurement up to 10μF</p> <p>Test leads conveniently store in case.</p> <p>12.2 x 3.8 x 5.5cm</p> <p>0.42kg</p>	1	pc(s)		
23	<p>2HP Direct Couple Air Compressor</p> <p>Motor: 2 hp</p> <p>Max. Pressure: 115 psi</p> <p>Displacement: 3.7 cfm</p> <p>Tank Capacity: 25 liters</p>	1	pc(s)		

24	Brass Manifold Gauge For R-12/22/134A WITH SIGHT GLASS & 36" HOSE	1	pc(s)		
25	GAUGE MANIFOLD FOR R410A Refrigerant: R410a with 3 sets of hose	1	pc(s)		
26	Gauge MANIFOLD FOR R32	1	pc(s)		
27	T-Handle Hex Key Set with Stand *The alloy steel shafts on these tools are treated by heat to ensure the tools are smooth and heavy duty. *The plastic grips on this hex key wrench set add comfort while you are holding them and make it easy to turn. *2-10mm (10) - 2,2.5,3,4,4.5,5,5.5,6,8,10MM	1	pc(s)		
28	MINI TUBE CUTTER FEATURES: Easy to use Cutting size: approx 1/8 - 5/8" Cuts soft copper , brass , aluminum, metal pipes Suitable for small space Light to carry around	1	pc(s)		
29	FLAIRING TOOL SET SPECIFICATIONS: Set of 6 CAP: 3/16", 1/4", 5/16", 3/8", 1/2", 5/8" WITH TUBE CUTTER & TUBE BENDERS	1	set(s)		
30	De Soldering Pump Features: Large barrel for powerful suction. Come with auto-clean pins for cleaning more solder.Light weight and easy for use. Imported piston pump,powerful suction. High-temperature proof, metabolic. Manual and easy operation.	2	pc(s)		
31	SOLDERING IRON 30 WATTS 220V soldering iron With Long Life Tip Light Grip Easy to Use	1	pc(s)		
32	SOLDERING IRON 60 WATTS 220V soldering iron With Long Life Tip Light Grip Easy to Use	1	pc(s)		
33	SOLDERING IRON 100 WATTS 220V soldering iron With Long Life Tip Light Grip Easy to Use	1	pc(s)		
34	Industrial Mapp Gas Torch	1	pc(s)		
35	Copper Tube Bender Designed to easily bend three different sizes of soft copper tubing with the same tool. Ideal for plumbing and HVAC applications. A 90° start angle minimizes effort required to form a bend. Handy reference marks indicate the angle for quick bends through 90°.	1	pc(s)		
36	ADJUSTABLE WRENCH 12 INCHES	1	pc(s)		
37	ADJUSTABLE WRENCH 6 INCHES	1	pc(s)		
38	Nut Driver Set (6-11mm) 5pcs	1	set(s)		

39	<p>T WRENCH LONG 8MM Socket T-wrench that can tighten and loosen bolts, rail wrenches and various other tools. The product has been manufactured in forged special steel and galvanized to give the user a longer durability.</p>	1	pc(s)		
40	<p>T WRENCH LONG 9MM Socket T-wrench that can tighten and loosen bolts, rail wrenches and various other tools. The product has been manufactured in forged special steel and galvanized to give the user a longer durability.</p>	1	pc(s)		
41	<p>T WRENCH LONG 10MM Socket T-wrench that can tighten and loosen bolts, rail wrenches and various other tools. The product has been manufactured in forged special steel and galvanized to give the user a longer durability.</p>	1	pc(s)		
42	<p>T WRENCH LONG 11MM Socket T-wrench that can tighten and loosen bolts, rail wrenches and various other tools. The product has been manufactured in forged special steel and galvanized to give the user a longer durability.</p>	1	pc(s)		
43	<p>T WRENCH LONG 12MM Socket T-wrench that can tighten and loosen bolts, rail wrenches and various other tools. The product has been manufactured in forged special steel and galvanized to give the user a longer durability.</p>	1	pc(s)		
44	<p>T WRENCH LONG 13MM Socket T-wrench that can tighten and loosen bolts, rail wrenches and various other tools. The product has been manufactured in forged special steel and galvanized to give the user a longer</p>	1	pc(s)		
45	<p>T WRENCH LONG 14MM Socket T-wrench that can tighten and loosen bolts, rail wrenches and various other tools. The product has been manufactured in forged special steel and galvanized to give the user a longer durability.</p>	1	pc(s)		
46	<p>T WRENCH LONG 17MM Socket T-wrench that can tighten and loosen bolts, rail wrenches and various other tools. The product has been manufactured in forged special steel and galvanized to give the user a longer durability.</p>	1	pc(s)		
47	<p>THHN WIRE SIZE 2.0 MM 150 meters Electrical Stranded Features</p> <ul style="list-style-type: none"> • CT-rated lead-free THHN/THWN cables are insulated with special PVC formulation that makes it more flame retardant than ordinary THHN cables. • More tolerant to heat with its better flameretardant PVC. • The insulation is made of materials that do not contain lead as stabilizer making it "environment friendly". • The nylon jacket offers mechanical protection and resistance to petroleum byproducts, chemical reagents, and oils. It is also abrasion-resistant, allows higher gliding and greater ease in installation 	2	box(es)		

48	<p>THHN WIRE SIZE 3.5 MM 150 meters Electrical Stranded Features</p> <ul style="list-style-type: none"> • CT-rated lead-free THHN/THWN cables are insulated with special PVC formulation that makes it more flame retardant than ordinary THHN cables. • More tolerant to heat with its better flameretardant PVC. • The insulation is made of materials that do not contain lead as stabilizer making it "environment friendly". • The nylon jacket offers mechanicalprotection and resistance to petroleum byproducts, chemical reagents, and oils. It is also abrasion-resistant, allows higher gliding and greater ease in installation 	2	box(es)		
49	<p>THHN WIRE SIZE 5.5 MM 150 meters Electrical Stranded Features</p> <ul style="list-style-type: none"> • CT-rated lead-free THHN/THWN cables are insulated with special PVC formulation that makes it more flame retardant than ordinary THHN cables. • More tolerant to heat with its better flameretardant PVC. • The insulation is made of materials that do not contain lead as stabilizer making it "environment friendly". • The nylon jacket offers mechanicalprotection and resistance to petroleum byproducts, chemical reagents, and oils. It is also abrasion-resistant, allows higher gliding and greater ease in installation 	2	box(es)		
50	<p>THHN WIRE SIZE 8.0 MM 100 meters Electrical Stranded Features</p> <ul style="list-style-type: none"> • CT-rated lead-free THHN/THWN cables are insulated with special PVC formulation that makes it more flame retardant than ordinary THHN cables. • More tolerant to heat with its better flameretardant PVC. • The insulation is made of materials that do not contain lead as stabilizer making it "environment friendly". • The nylon jacket offers mechanicalprotection and resistance to petroleum byproducts, chemical reagents, and oils. It is also abrasion-resistant, allows higher gliding and greater ease in installation 	1	box(es)		
51	<p>Retractable Utility Knife Optimized grip designed for comfort Push button blade change for easy blade change Nose of the knife features an exposed blade step to speed up blade placement Integrated, secure 10-blade storage</p>	1	pc(s)		
52	<p>Automatic Wire Stripper Stripper diameter:0.5mm~6mm With cutting function</p>	1	pc(s)		
53	<p>Finishing Sander -Pad Size: 4-1/2" x 4" -Abrasive Paper Size: 4-1/2" x 5-1/2" -Orbits Per Minute: 14,000 OPM -AMPS: 2 -Vibration (m/s²): 4 -Dimensions (LxWxH): 5-1/8" x 4-3/8" x 5-9/16"</p>	1	pc(s)		

	-Net Weight 2.5 lbs. -200W				
54	Comfort Grip Gloves -Nitrile Foam Coated Gloves which provides excellent grip, even in wet or oily conditions -EN388 4122 for great resistance to abrasion with limited tear and puncture resistance. -Elastic knit wrist cuff is easy to pull on and off quickly and keeps out debris -Long-lasting, durable and washable. -Application: Assembly, Maintenance, Plumbing, Logistics	9	pc(s)		
55	Safety Shoes -Industrial Safety Shoes -High Cut -CE approved EN20345-S1P -Steel toe cap -Steel midsole -Anti-static & Anti-Vibration & Oil resistant & Slip resistant -Split leather upper -Dual density pu sole	3	pair(s)		
56	Safety Boots -CE approved EN20345-S5 -Material: PVC -Steel toe cap and steel midsole -High level oil, acid, alkali resistance , 100% waterproof -Desludging shoe sole -Packing: poly bag with color label	3	pair(s)		
57	Rain Coat Top -Light -Compact -Waterproof -Breathable	5	pc(s)		
58	Rain Coat Pants -Light -Compact -Waterproof -Breathable	5	pc(s)		
59	Welding Gloves -Material: Cow split leather -Lengthened for better protection -With half lining -Packed by paper hanger	3	pair(s)		
60	Brick Laying Trowel -Industrial Bricklaying Trowel -Diameter of connecting rod: 9.5mm -Two-component plastic handle -5" inches	2	pc(s)		
61	Plastering Trowel -Plastic handle -Stainless steel -280x120mm	2	pc(s)		
62	Round Point Shovel -Heavy Duty -Steel	2	pc(s)		
63	Spade Shovel -Heavy Duty -Flat Metal Blade -Steel	2	pc(s)		
64	Pull Push Rule -Length: 5 meters -Blade Width: 3/4 inch -Steel Tape Measure	2	pc(s)		

65	<p>Laser Measuring Device SPECIFICATIONS: Dust and splash protection IP 65 Measurement time, typical < 0.5 s Units of measurement m/cm, ft/inch Laser diode 515 nm, < 1 mW Measurement range 0.05 – 50.00 m Laser class 2 Measurement accuracy, typical ± 1.5 mm* (*plus usedependent deviation) Measurement range of incline measurement 0 – 360° (4 x 90°) Measuring accuracy (typical) ± 0.2** (*plus usedependent deviation) Measurement time, max. 4 s Power supply 2 x 1.5 V LR6 (AA) Automatic deactivation 5 min Weight, approx. 0.2 kg Memory capacity (values) 30 Tripod thread 1/4" Laser colour Green Measuring range, up to 50 m</p>	1	pc(s)		
66	<p>400 IGBT DC Inverter ARC Welding Machine with case Insulated stainless steel body construction Single phase, portable, fan cooled Low energy consumption, light in weight with handle for easy handling Good arc starting and arc force Step less current adjustment Stable performance, continuous work, automatic compensation for voltage fluctuation Great quality welding, deep melting pool, reliable effect Over current / over voltage protection Specifications: Power Voltage: 220V Output Current: 400 Amperes Current Range: 20-400 Amperes Enclosure Class: IP21 Insulation Class: F With Air Cool function</p>	1	pc(s)		
67	<p>Digital Inverter Gasless MIG + MMA + TIG 3 in 1 Welding Machine 300 Digital Inverter Gasless MIG + MMA + TIG 3 in 1 Welding Machine Low Power Consumption High Efficient Higher output (%) 15% to 20% more than other machines. Light Weight, Compact and Portable Easy to Operate and safe to use Low Maintenance Inverter IGBT NO GAS MIG / MAG + MMA (ARC) + LIFT TIG 3 in 1 Welding Machine. Model: YMG-300 Voltage: 220V Frequency: 60Hz No-Load Voltage: 60V Rated Input Capacity: 6KVA Output current: MIG: 30-300A, MMA: 20-300A, TIG: 10-300A Fluxed cored wire Diameter (MIG): 0.8 - 1.0mm Applied Welding Rod (MMA): 1.6 - 3.2mm Applied Welding Tungsten (TIG): 1.0 - 2.0mm Rated Duty Cycle: 60%</p>	1	pc(s)		
68	<p>Cordless Angle Grinder 100mm (4") 18V LXT® Li-Ion SPECIFICATIONS: Wheel Diameter 100 mm (4") No Load Speed (RPM) 11,000 Dimensions (L x W x H) 317x118x118 mm (12-1/2"x4-5/8"x4-5/8") Net weight 1.90 – 2.51 kg (4.19 – 5.54 lbs) INCLUDES: Grinding Wheel, Wheel Cover, Side Handle, Lock Nut Wrench, Battery, Charger</p>	1	pc(s)		

69	<p>Cordless Hammer Driver Drill 3/8 Max12V SPECIFICATIONS: Capacity Steel / Wood / Masonry: 10 / 21 / 8 mm (3/8" / 13/16" / 5/16") Chuck Capacity 0.8 – 10 mm (1/32 – 3/8") Impacts Per Minute (IPM) High / Low: 0 – 25,500 / 0 – 6,750 No Load Speed (RPM) High / Low: 0 – 1,700 / 0 – 450 Max Fastening Torque Hard / Soft: 30 / 14 N·m (270 / 130 in.lbs.) Max lock torque 28 N·m (250 in.lbs.) Max Output 170 W Clutch torque setting 0.5 – 3.5 N·m (4 – 30 in.lbs.) Vibration Level Impact Drilling into Concrete: 13.0 m/s² Vibration K Factor Impact Drilling into Concrete: 1.5 m/s² Vibration Level Drilling into Metal: 2.5 m/s² or less Vibration K Factor Drilling into Metal: 1.5 m/s² Sound Pressure Level 82 dB(A) Sound Power Level 93 dB(A) Noise K Factor 3 dB(A) Dimensions (L x W x H) w/ BL1016/BL1021B: 193x66x212 mm (7-5/8"x2-5/8"x8-3/8") w/ BL1041B: 193x66x229 mm (7-5/8"x2-5/8"x9") Net weight 1.1 – 1.3 kg (2.4 – 2.9 lbs.)</p>	1	pc(s)		
70	<p>Cordless Driver Drill 18V G-Series 13mm (1/2") Kit Set SPECIFICATIONS: Max Fastening Torque: Hard / Soft: 42 / 24 N·m No Load Speed (RPM) High / Low: 0 – 1,400 / 0 – 400 Includes: 2x1.5Ah Batteries and 1 Charger All metal gear construction ensures high transmission durability Mechanical 2-speed gearing; High speed mode for speedy drilling in light duty applications; Low speed mode for heavy duty applications requiring high torque Variable speed control dial enables user to match the speed to the application 16 clutch settings and drill mode for added fastening control Single sleeve keyless chuck allows for easy bit installation/removal with one hand Rubberized soft grip provides more control and reduced fatigue Compact and lightweight design for easy handling and high maneuverability Low noise level for improved user comfort Electric brake for maximum productivity and increased operator safety</p>	1	pc(s)		
71	<p>Cordless Jigsaw Max12V CXT Kit Set Features: Slide type Li-ion battery 3 orbital settings plus straight cutting Electric brake Variable speed trigger control Ergonomically designed handle Blower function - blows sawdust off the line cut Rigid aluminium base bevels 0 to 45 degrees left and right Connectable to dust extractor with correct attachment Inclusions: 1 x Cordless Jigsaw 2 x Battery 1.5Ah 1 x Charger 1 x Jigsaw Blade 1 x Hex Wrench 1 x Guide Rule 1 x Carrying case</p>	1	pc(s)		
72	<p>4-Way Staple Gun Tacker / Stapler Gun Durable all steel construction Built-in staple remover Rear loading system for ease of use and jam clearing Power adjustment control system Low staple refill window Safety lock handle</p>	2	pc(s)		

	Loading Capacity:- 125 PCS Staples- 70 PCS Nail Pin- 70 PCS U Type				
73	Rubber Mallet Specifications: 450g/16oz Rubber Hammerhead Fiberglass Handle	2	pc(s)		
74	Deadblow Mallet 2lbs Specifications: Fiberglass Handle Dead Blow Mallet Weight 2LB Non-marring plastic faces Non-rebounding Non-spark	2	pc(s)		
75	Heavy Duty Hand Riveter FEATURES: Tempered steel alloy construction Soft rubber non slip grip insulated handle Rivets capacity : 2.4, 3.2, 4.0, 4.8 mm Rivet tool adopts steel gripping head and full hardened claws 17" long tubular arm handle give extra leverage	1	pc(s)		
76	Level Bar FEATURES: Aluminum 48 inches Top-read center vial designed for easy readability. Shock-absorbing end caps hold up to heavy use Hang hole simplifies storage. Pipe groove allows use on round objects. Durable lightweight aluminum construction suite to all purpose use. Top-read center vial designed for easy readability. Shock-absorbing end caps hold up to heavy use Hang hole simplifies storage. Pipe groove allows use on round objects. Durable lightweight aluminum construction suite to all purpose use.	2	pc(s)		
77	Industrial Tool Bag Specifications: -17 in. -Rigid frame for easy opening and access -Special partition of the internal and external pockets, -Easy access to the tool compartment -Adjustable shoulder strap included -Light weight fabric box	1	pc(s)		
78	Solid Brass Plumb Bob Features: 8oz Polished-lacquer, solid-brass construction is durable and rust resistant Replaceable, hardened steel tip is long-lasting Screw top simplifies attaching string to center of plumb Comes with extra tip Through hole for easy tightening	1	pc(s)		
79	Lock Installation Kit Set FEATURES: Set to drill holes and install lock on wood door. Sharp hole saws can drill round holes easily and quickly. Hole Saw Drill Cutter / Auger Bit Made of high carbon steel Suitable for cutting solid wood, fiber board, veneered board, particle board, plywood, etc. Great for spherical door lock perforation Suitable for ball type door lock hole	1	pc(s)		
80	Nail Bag	2	pc(s)		

81	VACUUM CLEANER <i>*1200w max power for efficient performance</i> <i>*Durable body for wet and dry applications</i> <i>*10L large tank capacity for less frequent dust disposal</i> <i>*Blower function for extra cleaning convenience</i> <i>*Easy to assemble hose & tubes for quick set up</i> <i>*Wheels detachable handheld</i>	1	pc(s)		
82	RATCHET CABLE CUTTER <i>*Cutting Range: 380mm²</i> <i>*Compact and lightweight, easily carried anywhere, and can be used anytime!</i> <i>*Easily cut copper wires and aluminum wires with minimum effort</i>	1	pc(s)		
83	A - TYPE FIBERGLASS STEP LADDER 6 FEET <i>*Miller Fiberglass A-Type Step Ladder (Orange) (A Type)</i> <i>*Color: Orange</i> <i>*Made in USA</i>	1	pc(s)		
84	A - TYPE FIBERGLASS STEP LADDER 10 FEET <i>*Miller Fiberglass A-Type Step Ladder (Orange) (A Type)</i> <i>*Color: Orange</i> <i>*Made in USA</i>	1	pc(s)		
85	PROFESSIONAL HEAT GUN (2000W) <i>*2 speed heat gun with variable heat control giving maximum control in all heat gun applications</i> <i>*Both hands can be free for soldering or bending operations</i> <i>*Ergonomic handle design for comfortable use even over extended periods of time.</i> <i>*Lock-on switch for continuous use applications</i> <i>*Power Input : 2000 W</i> <i>*Air Flow (l/min) : 300/500</i> <i>*Operating Temperature (°C) : 50-450 / 90-600</i>	1	pc(s)		
86	NON CONTACT VOLTAGE TESTER <i>*Non-contact detection of voltage in cables, cords, circuit breakers, lighting fixtures, switches, outlets, and wires.</i> <i>*High intensity, bright green LED indicates the tester is operational and aids in illuminating the workspace.</i> <i>*When voltage is detected, a high intensity, bright red LED illuminates and a warning tone sounds.</i> <i>*CAT IV 1000 Volt safety rating provides expanded operation and protection.</i> <i>*50 to 1000 Volt AC power operating range allows broad application.</i> <i>*Durable polycarbonate plastic resin construction.</i> <i>*Package contains insert card w/ integrated owner's manual and 2 AAA 1.5 volt batteries.</i>	2	pc(s)		
87	BROTHER PT-D210 ELECTRONIC LABELLER <i>*One-touch keys for easy label creation</i> <i>*Graphical LCD display</i> <i>*Print up to 12mm TZe laminated tapes width</i> <i>*20mm per second fast print speed</i> <i>*Print up to 2 lines</i> <i>*12 Deco mode designs for 12mm tapes</i> <i>*KEYBOARD: QWERTY</i> <i>*MEDIA TYPE: TZe Tape</i> <i>*AVAILABLE TAPE WIDTHS: 3.5, 6, 9, 12mm</i> <i>*PRINT RESOLUTION: 180 dpi</i>	1	pc(s)		
88	HYDRAULIC CRIMPING TOOL 18X 475mm <i>*Crimping range: Cu 16-240mm²</i> <i>*Crimping force: 70kN</i> <i>*Crimping type: hexagon crimping</i> <i>*Stroke: 18mm Length: approx 475mm</i> <i>*Weight: approx 3.6kg Weight of box: approx 1.8kg</i> ACCESSORIES <i>*Crimping dies: 16,25,35,50,70,95,120,150,185,240mm²</i> <i>*Sealing O-ring: one set</i>	1	pc(s)		
89	380 TWO WAY WALKIE TALKIE <i>*Model: HX-380</i> <i>*Large color display</i>	2	pc(s)		

	*LED strong flashlight *Dual frequency/dual display/dual standby *High capacity lithium battery 5500mAh, standby for up to 40 hours *CTCSS/DCS encoding and decoding function *Line transceiver frequency: 136-174/400-520MHZ *Transmitting and transmitting power: 10W *Memory channel: 999 *Size: 6cm (W) × 12cm (H) × 3.5cm (D) *Weight: 240g (including battery and antenna)				
90	Electrical/Electronic Contact Cleaner Blasts away oil, dirt, flux residue and condensation from sensitive electronics and electrical equipment with pinpoint precision. It dries quickly, leave no residue and removes more soil than leading competitors, making it the best at cleaning electrical contacts. Safe to use and 50-state VOC compliant, it's ideal for use on printed circuit boards, controls, switches, precision instruments and electric panels.	12	pc(s)		
	nothing follows				
	-				
	LOT ABC - Php 312,661.89				
	-				

Brand and Model : _____
 Warranty : _____

Delivery Period : _____
 Price Validity : _____

After having carefully read and accepted your General Condition, I/We quote you on the items at prices noted above.

CERTIFICATION

I hereby certify that I have personally conducted this canvass and that the price(s) quoted is/are true & correct and the signature of the representative of the company who submitted the quotation(s) is/are genuine.

POSTED TO PHILGOPS
 Printed Name & Signature of Authorized Canvasser

 Printed Name / Signature

 Tel. No. / Cell phone No.

 E-mail address

 Date

 Tin Number

URS-AF-AS-PRO-F-2017-02

Rev. 00

Effectivity Date August 15, 2017

Modified version of RFQ form
 (SF-GOOD-60, May 2004)

RFQ-2024-06-0569
 PR-2024-06-0815
 END USER: JOHN ANDREW FRANCISCO