



Republic of the Philippines
UNIVERSITY OF RIZAL SYSTEM

Province of Rizal
Cp No. (63)918-9519618
urs.bacsecretariat2020@gmail.com

Date : December 10, 2024

Company/Supplier Name : _____

Address : _____

Please quote your lowest price on the item/s listed below, subject to the General Conditions on the last page, stating the shortest time of delivery and submit your sealed quotation duly signed by your representative not later than **12/16/24** to URS SPMO, Morong Rizal.


ARIEL M. PLANTILLA, DBA
Chairperson, BAC

NOTE: 1. ALL ENTRIES MUST BE TYPEWRITTEN 2. DELIVERY PERIOD WITHIN 30 CALENDAR DAYS 3. WARRANTY SHALL BE FOR A PERIOD OF SIX (6) MONTHS FOR SUPPLIES & MATERIALS, ONE (1) YEAR FOR EQUIPMENT, FROM DATE OF ACCEPTANCE BY THE ENTITY
4. PRICE VALIDITY SHALL BE FOR A PERIOD OF 45 CALENDAR DAYS
5. G-EPS REGISTRATION CERTIFICATE SHALL BE ATTACHED UPON SUBMISSION OF THE QUOTATION
6. BIDDERS SHALL SUBMIT ORIGINAL BROCHURES SHOWING CERTIFICATIONS OF THE PRODUCT BEING OFFERED

ITEM NO.	ITEM & DESCRIPTION	QTY.	UNIT	BID PRICE	TOTAL BID PRICE
1	<i>COLUME 306 & ACTIVE 15</i> <i>2x6*3" Full range Speaker 25mm voice coil</i> <i>2x1*15" Active woofer 75mm voice coil</i> <i>1300w Built-in Amplifier.</i> <i>With tour case</i> <i>SZ12 12 Channel Digital Mixer</i> <i>Bnew and Original</i> <i>12 Channel, 6 AUX, 1 stereo main and 1 stereo monitor channel</i> <i>Digital interface: one way for optical and one way for USB audio (output or input) USB play or USB rec</i> <i>BT interface with BT music playback</i> <i>No of matrices and buses: 12x14 matrices, 14 buses</i> <i>Headphone jack: 2xtp.s</i> <i>Pusher: 10 pcs of 100mm electric pusher encoder: 360 rotary encoder</i> <i>AD/DA sampling rate: 24 bit, 192KHz</i> <i>signal processing accuracy: 32 bit floating point 48KHz</i>	1	set(s)		
2	<i>Eq: input 4 segments, effects channel 4 segments and output 7 segments</i> <i>Effector: double effect channel, 32+32 kinds</i> <i>Signal processing: full dynamic processing</i> <i>Screen: 7" capacitive touch screen Storage: full parameter storage for 12 scenarios</i> <i>Phantom power supply: 49V 8 way independent control</i> <i>USB playback: full list screen display, touch operation</i> <i>Noise gate: each channel is independently controlled, -80db can be set to 0 dB Freq response; +0.5/-1.0 dB</i>	1	pc(s)		

	AD ACT 9090 DUAL WIRELESS MICROPHONE MIC PROFESSIONAL QUALITY MICROPHONE ORIGINAL				
3	Sensitivity(peak deviation) 3uV(52dB S/N) AF output clipping level: Balanced outputs:+10dB(XLR) Unbalanced outputs:+4dB(1/4" 6.3mm jack socket) Adjacent channel interference ratio: 80dB Image interference Ratio:80dB RF Outputs:8mW-30mW Harmonic suppression:>50dB Black	1	pc(s)		
4	Patch cable microphone wire (heavy duty)	1	pc(s)		
5	Xlr connector male and female	12	pair(s)		
6	Power Distribution Unit PDU Extension Unit 12 Socket Overload Protection + Switch 2Meter Extension Cord voltage range: 110-250V Current rating: 16A 3500W rated power: 50-60HZ shell material:aluminum alloy shell+ PC material Line length: 2M Line core: 3*1.5mm2	1	pc(s)		
7	Panasonic Eneloop Pro BK 3HCCE 4BT AA Rechargeable Battery Pack of 4 (Black)	2	pack(s)		
8	Heavy duty speaker stand crank type	2	pc(s)		
9	4 Channel 3 Pin Multi Network XLR Cable for Stage Sound Lighting and Recording Studio Male and Female To RJ45 Ethercon NE8F-4M (1)High quality aluminum alloy (2)NEUTRIK connectors (3) Transmits 4 channels of balanced analogue, AES or DMX signal (4)Connects to ethercon cat6 network cable [up to 330 feet] (5)Compatible with 3-pin XLR based systems (7)Connect up to 4 separate lines down a single cat6 cable (Experience exceptionally clear, balanced, interference-free sound (9)Keep your lines extra organized and protected in studio and on stage. (10) Use your versatile connector for a variety of audio and video applications 2x 12" Active Monitor Speaker System 800W Class D Amplifier	2	pc(s)		
10	Wave guide Horn 70" x 40" Low 3" Vcoil Hi 1.7 Vooil 8 ohms Max SPL 122dB, 128dB Peak Freq. Resp. 60Hz-20KHz Size: 45(W) x 46(D) x 33(H)cm	1	pair(s)		
11	DMX Lighting Controller	1	pc(s)		
12	XZ-20 Dual 10 woofer x2, 500w, 8 ohms, 101dB, 20Hz-20KHz	4	pc(s)		
13	XZ-1820 5UB 1000watts, 8 Ohms, 55Hz-1KHz, 98 dB, 18" Woofer SZ12 12 Channel Digital Mixer Bnew and Original 12 Channel, 6 AUX, 1 stereo main and 1 stereo monitor channel Digital interface: one way for optical and one way for USB audio (output or input) USB play or USB rec BT interface with BT music playback No of matrices and buses: 12x14 matrices, 14 buses	2	pc(s)		

	<p>Headphone jack: 2xtp.s</p> <p>Pusher: 10 pcs of 100mm electric pusher encoder: 360 rotary encoder</p> <p>AD/DA sampling rate: 24 bit, 192KHz</p>				
14	<p>Signal processing accuracy: 32 bit floating point 48Khz</p> <p>Eq. input 4 segments, effects channel 4 segments and output 7-segments</p> <p>Effector: double effect channel, 32+32 kinds</p> <p>Signal processing: full dynamic processing</p> <p>Screen: 7" capacitive touch screen</p> <p>Storage: full parameter storage for 12 scenarios</p> <p>Phantom power supply: 49V 8 way independent control</p> <p>USB playback: full list screen display, touch operation</p> <p>Noise gate: each channel is independently controlled, -80db can be set to 0 dB</p> <p>Freq response; +0.5/-1.0 dB</p> <p>AD ACT-9090 DUAL WIRELESS MICROPHONE MIC PROFESSIONAL QUALITY MICROPHONE ORIGINAL</p>	1	pc(s)		
15	<p>Sensitivity(peak deviation) :3uV(52dB S/N)</p> <p>AF output clipping level.</p> <p>Balanced outputs:+10dB(XLR)</p> <p>Unbalanced outputs:+4dB(1/4" 6.3mm jack socket)</p> <p>Adjacent channel interference ratio: 80dB</p> <p>Image interference Ratio:80dB</p> <p>RF Outputs:8mW~30mW</p> <p>Harmonic suppression:>50dB Black</p>	1	pc(s)		
16	<p>4 Channel 3 Pin Multi Network XLR Cable for Stage</p> <p>Sound Lighting and Recording Studio Male and Female To RJ45 Ethercon NE8F-4M</p> <p>(1)High quality aluminum alloy</p> <p>(2)NEUTRIK connectors</p> <p>(3)Transmits 4 channels of balanced analogue, AES or DMX signal</p> <p>(4)Connects to ethercon cat6 network cable (up to 330 feet]</p> <p>(5)Compatible with 3-pin XLR based systems</p> <p>(7)Connect up to 4 separate lines down a single cat6 cable</p> <p>(8)Experience exceptionally clear, balanced, interference-free sound</p> <p>(9)Keep your lines extra organized and protected in studio and on stage</p> <p>(10) Use your versatile connector for a variety of audio and video applications.</p>	4	pc(s)		
17	<p>Patch cable microphone wire (heavy duty)</p>	2	pc(s)		
18	<p>Xlr connector male and female</p>	12	pair(s)		
19	<p>Power Distribution Unit PDU Extension Unit 12</p> <p>Socket Overload Protection + Switch 2Meter</p> <p>Extension Cord</p>	1	pc(s)		

	voltage range: 110-250V Current rating: 16A 3500W rated power: 50-60HZ shell material:aluminum alloy shell+ PC material Line length:2M Line core: 3*1.5mm2				
20	3in1 RGB LED PAR 3 watts x 54 Bulb Full Color with Link Cables	16	pc(s)		
21	Big Dipper LC003-H Amber white with Loop Cable	8	pc(s)		
22	100 meters DMX Cable AWG24 Cord (DMX001L1000)	1	roll(s)		
23	Panasonic Eneloop Pro BK 3HCCE 4BT AA Rechargeable Battery Pack of 4 (Black) Original	2	pack(s)		
24	NEUTRIK Type NL4FX Speakon 4Pole Plug Male Audio Speaker Connectors CONNECTOR	20	pc(s)		
25	4 Channel amplifier, 8 Ohms Stereo power 4x1000w, 4 Ohms Stereo power 4x1500w, 8 Ohms Stereo bridge 2x3000w, 4 Ohms Stereo bridge 2x3900w	1	pc(s)		
26	DriveRack PA2. Complete Loudspeaker Management System Specifications Input(2) line inputs. (1) RTA Mic input Input Connectors(2) Female XLR line inputs. (1) Female XLR RTA Mic input Input TypeElectronically balanced/RF filtered Input Impedance>50 kohm A/D Converterdbx Type IV Conversion System CMRR> 45dB Mic Preamp Phantom Power+15VDC (RTA) Mic Preamp Equivalent Input Noise (EIN)110 dB A- weighted, >107dB unweighted THD+Noise0.003% typical at +4dBu, 1kHz, OdB input gain Frequency Response20Hz-20kHz, +/- 0.5dB Interchannel Crosstalk<-110 dB, -120dB typical (input-to-output: <-100 dB) Operating Voltage 100-120VAC 50/60 Hz - EU: 220-240 VAC 50/60 Hz Power Consumption22 W Unit Weight5.25 lbs. (2.4 kg) Shipping Weight6.75 lbs. (3.1 kg) Dimensions1.75" (H) x 5.75" (D) x 19" (W), 4.4cm (H) x 14.6cm (D) x 48.26cm (W) D/A Dynamic Range112 dB A-weighted, 110dB unweighted (dbx Driverack PA2 copy)	1	pc(s)		
27	14/4 Royal Cord (100M) Coated Copper Aluminum	1	roll(s)		
	nothing follows				
	-				
	LOT ABC - Php 548,580.00				
	-				

Brand and Model : _____
Warranty : _____

Delivery Period : _____
Price Validity : _____

After having carefully read and accepted your General Condition, I/We quote you on the items at prices noted above.

CERTIFICATION

I hereby certify that I have personally conducted this canvass and that the price(s) quoted is/are true & correct and the signature of the representative of the company who submitted the quotation(s) is/are genuine.

Printed Name / Signature

Tel. No. / Cell phone No.

E-mail address

Date

Tin Number

POSTED to PHILGEPS

Printed Name & Signature of Authorized Canvasser

URS-AF-AS-PRO-F-2017-02

Rev. 00

Effectivity Date August 15, 2017

Modified version of RFQ form
(SF-GOOD-60, May 2004)

RFQ-2024-12-1035
PR-2024-11-1719 PR-2024-11-1720
END USER: JOY SG. CRUZ

Note: Mandatory documents
**Delivery Receipt*
**Service/Billing/Sales Invoice*
**Official/Collection Receipt*
**Philgeps registered atleast RED membership*
(Above 50k)
**Mayor's Permit*
**Tax Clearance/ BIR 2303*
**DTI Certificate*