Technical Specifications

Steno Machine

| Item | Specifications | Statement of Compliance |
|---|---|-------------------------|
| 1.Steno Machine, 1 unit brand new and complies with the following equivalent of higher specification: | ABC – P 352,000.00 | |
| 1.1 | Steno Machine with EasyLock tripod 12.5" folded 27" extended, charger, new Ni-CAD battery | |
| 1.2 | Folds face down to protect screen while not in use | |
| 1.3 | Display screen: Active matrix color TFT- LCD, Diagonal: 7" (17.8 cm), Resolution: 800 x 480, Tilt range 180 degrees, Font size 1 to 5 | |
| 1.4 | CSE Writer Dimension Weight 3.5lbs Height 2.5" | |
| 1.5 | Supports SD cards 1GB to 32GB, 64 MB internal memory hold approximately 36,000 pages. | |
| 1.6 | USB Port: Client USB connects to a Host USB port on a computer for: Realtime translation with Case CATalyst® and other brands, Downloading dictionaries, Accessing a power source | |
| 1.7 | Host USB port for use with peripherals such as a thumb drive or USB Bluetooth™ adapter for wireless realtime. | |
| 1.8 | Automatic switching 120/220 volt | |
| 1.9 | 3.5 mm mono headphone & microphone jack | |
| 1.10 | 4-cell lithium-ion battery pack is included | |
| 1.11 | Including Laptop for workstation | |
| 1.12 | With Bag and standard accessories | |
| 1.13 | Include the product brochure of the item being offered | |
| 1.14 | With two (2) years on-site warranty with life time free service warranty | |
| | | |